



## G SERIES, XENON STROBE BEACON, Ø120MM

842531313

Xenon strobe beacon, Ø120mm, Amber, 230-240 V AC, FLG

- Ø120mm Beacon
- Strobe, Flashing and Steady light options
- Wide control voltage range



### PRODUCT DESCRIPTION

The Series G is AUER's best-value solution for universal applications. The large signal lamp with 48 LEDs produces an excellent frontal and lateral signal effect. The surface-mounted beacon series is available in the size Ø 120 mm with a low calotte. With an ingress protection class of IP65, the G series surface-mounted beacon is recommended for outdoor use.

Mounting options include vertical mounting, this model also contains a bayonet locking system with push button. It is used for general applications due to its attractive price to performance ratio.

## TECHNICAL DATA

### GENERAL DATA

Lens colour	Orange
Light type	Strobe
Light source	Xenon
Housing Colour	Black RAL 9005

### RATED OPERATING CONDITIONS

Nominal Supply Voltage	230-240 V AC
Nominal current	100 mA
Flash energy	5 J
Flash frequency	1 Hz
Operational temperature	-30°C ... 50°C
Terminal connection	2,5 mm <sup>2</sup>

DIMENSIONS

Height	102 mm
Diameter	120 mm

ADDITIONAL DATA

IP class	IP65
----------	------

