## **SIGNAL TOWER, HALF DOME 90**

H90K0243AGD Signal tower,HALFDOME 90 24V AC/DC



- Compact (ready to use) LED signal tower in half dome design
- Tower is built and supplied according to customer's requirements
- Wide control voltage range



## PRODUCT DESCRIPTION

The Half Dome 90 signal tower is a high quality option for signalling, with a pleasing look and 180° viewing angle the Half Dome is perfect for any high end signalling requirements.

- Visual-audible LED signal tower in half dome design
- For universal applications (industrial, building and others)
- Any colour combination and housing size (2 5 positions) available
- 6 lens colours, 3 housing colours (grey, chrome, black)
- LED steady light or LED flashing light for each position selectable
- High protection class IP 65 suitable for outdoor and indoor
- For horizontal and vertical mounting
- Particular lens optics with reflective coating
- optimal signalling and visibility from each viewing angle (180°)
- moving bright LED light
  - Optional piezo buzzer in upper housing area available
- tone types continuous and pulsing
- sound pressure individually adjustable ~70-90 dB (A)at 1M
  - SPS-fit (leakage, inrush current)
  - Available in nominal voltages 12 V ac/dc, 24 V ac/dc, 110/120 V ac and 230/240 V ac
  - Certified to UL type 4/4X/13

## **TECHNICAL DATA**

## **DATA**

Lens colour	Green, Orange, Red
Housing Colour	Silver
IP class	IP65
Light source	LED
Light type	Green LED, Orange LED, Red LED

Supply voltage	24 V
Mounting	Wall
Nominal current max	0,043 A
Temperature operational min	-30 °C
Temperature operational max	50 °C
Nominal current min	0,043 A
Terminal connection	2,5 mm²
Diameter	90 mm



