

FPM-7211W-P3AE 21.5" Industrial Monitor, Touchscreen, Direct-VGA and DVI



- 10-fingers multitouch
- SECC Chassis with IP66 in front
- 16:9 Wide screen format
- 21,5"
- Panel mounted or welded



PRODUCT DESCRIPTION

The FPM-7000 Series is the most robust and industry-class screen in our range. With a full-length glass on the front, this monitor becomes IP66 classed and robust, which means that the frame does not feel and creates a significantly better overall impression than other series and models on the market.

With viewing angles and high brightness, this monitor is suitable for all types of applications

TECHNICAL DATA

| Approvals | CCC, CE, FCC, UL, BSMI |
|-----------------------|------------------------|
| | |
| Backlight | LED LCD |
| Contrast | 5000:1 |
| Depth | 47,7 mm |
| Display format | 16:9 |
| Display resolution | 1920x1080 |
| Display size | 21,5 " |
| Front panel thickness | 7 mm |
| Height | 349,8 mm |
| Hole size | 550,3x341,8 |
| IP class | IP66 |
| Luminance | 300 cd/m ² |
| Material front frame | Aluminium |

| Material protection | Zinc plated steel |
|-----------------------------|-------------------|
| Number of display colours | 16,7 |
| Power consumption | 25 W |
| Power supply | 24 V DC |
| Storage temperature max | 60 °C |
| Storage temperature min | -20 °C |
| Temperature operational max | 55 °C |
| Temperature operational min | 0 °C |
| Weight | 8 kg |
| Width | 558,4 mm |
| Viewing angle | 178/178 |

