



## ADVANTECH FPM-7061T MONITOR

FPM-7061T-R3AE

6.5" VGA Industrial Monitor, Touchscreen, Direct-VGA/DP

- 5-wire analog resistive touch
- SECC Chassis with IP66 in front
- 4:3 format
- 6,5"



### PRODUCT DESCRIPTION

The FPM-7000 Series is the most robust and industry-class screen in our range. With a full-length glass on the front, this monitor becomes IP66 classed and robust, which means that the frame does not feel and creates a significantly better overall impression than other series and models on the market.

With viewing angles and high brightness, this monitor is suitable for all types of applications

### TECHNICAL DATA

|                       |                        |
|-----------------------|------------------------|
| Approvals             | CCC, CE, FCC, UL, BSMI |
| Backlight             | LED LCD                |
| Contrast              | 600:1                  |
| Depth                 | 46,1 mm                |
| Display format        | 4:3                    |
| Display resolution    | 640x480                |
| Display size          | 6,5 "                  |
| Front panel thickness | 7 mm                   |
| Height                | 152 mm                 |
| Hole size             | 189,1x142,1            |
| IP class              | IP66                   |
| Luminance             | 800 cd/m <sup>2</sup>  |
| Material front frame  | Aluminium              |
| Material protection   | Zinc plated steel      |

|                             |         |
|-----------------------------|---------|
| Number of display colours   | 16,2    |
| Power consumption           | 10 W    |
| Power supply                | 24 V DC |
| Storage temperature max     | 70 °C   |
| Storage temperature min     | -30 °C  |
| Temperature operational max | 60 °C   |
| Temperature operational min | -20 °C  |
| Weight                      | 1,2 kg  |
| Width                       | 199 mm  |
| Viewing angle               | 160/140 |