



IDEM HLM-CBA TAPE CONVERGENCE SENSOR

174401

HLM-CBA with Plastic Roller M20 2NC 2NO

- 2 types of lever rollers
- Perfect for smaller conveyors
- Small dimensions
- Different contact configurations



PRODUCT DESCRIPTION

The offer of tape cone detectors in the Mini IDEM version complements a wide range of cable switches used for emergency stop along conveyors. They are mounted along the conveyor belt and indicate the crookedness of the conveyor belt. We offer standard models (casting made of metal) and made of stainless steel. The rollers of these breakers can be of plastic or stainless steel.

TECHNICAL DATA

Actuator	Plastic Roller
Approvals	ISO 14119, EN60947-5-1, EN60204-1, ISO 13849-1, EN62061, UL 508
ATEX approved	No
Conductor size	1,5 mm ²
Conduit entry	M20
Contact type	Without torque contact
Contacts	2NC 2NO
Electrical lifetime	100,000 cycle min. (at full load)
Housing material	Die cast metal
Integrated LED indication	No
IP class	IP67
Maximum switching speed	250 mm/s
Mechanical reliability B10d	500,000 operations at 100mA load
Minimum current	5V 5mA DC

Mounting	4 x M5
Operating temperature	-25°C...+80°C
PFHd	3,44x10 ⁻⁸
Rated insulation voltage	300 V AC
Thermal current (Ith)	10 A
Utilisation category	AC15
Vibration	IEC68-2-6 10-55Hz 0.35mm
Withstand voltage	2500 V AC

