



MT60 MONOLITHIC SIGNAL TOWER

MT60-F100-24V DC

24 V DC red/yellow/green, white with tube base

- Pre-assembled entry level signal tower for ready-to-go installation
- Excellent circular light distribution to prevent blind spots
- Transparent lens to prevent wrong signaling indication caused by external light interferences
- Easy cleaning of the monolithic single lens also powerful water jets possible (IP66)
- Fixed, seperared colour positions(green/yellow/red) with steady light and escalation options, including flashing red and/or sound



PRODUCT DESCRIPTION

TECHNICAL DATA

DATA

Lens colour	White
Housing Colour	White
IP class	IP66
Mounting	Pipe socket
Temperature operational min	-25 °C
Temperature operational max	50 °C
Nominal current	3 mA
IK class	7
Nominal Supply Voltage	24 V DC
Diameter	61 mm
Height	291 mm

INPUT		Terminal block	MT60-F100-... MT60-W-...	MT60-M12-24V DC	MT60-M12-S-24V DC
MT12 Male Connector PIN	Input				
3	0	common	common	common	
4	1	green steady	green steady	green steady	
1	2	yellow steady	yellow steady	yellow steady	
2	3	red steady	red steady	red steady	
5	4	red blinking	red blinking	tone pulsing	
	6	(optional)	-	-	

MT60 Dimension Drawing

