



G SERIES, XENON STROBE BEACON, Ø120MM

842531313

Xenon strobe beacon, Ø120mm, Amber, 230-240 V AC,
FLG

- Ø120mm Beacon
- Strobe, Flashing and Steady light options
- Wide control voltage range



PRODUCT DESCRIPTION

The Series G is AUERs best-value solution for universal applications. The large signal lamp with 48 LEDs produces an excellent frontal and lateral signal effect. The surface-mounted beacon series is available in the size Ø 120 mm with a low calotte. With an ingress protection class of IP65, the G series surface-mounted beacon is recommended for outdoor use.

Mounting options include vertical mounting, this model also contains a bayonet locking system with push button. It is used for general applications due to its attractive price to performance ratio.

TECHNICAL DATA

GENERAL DATA

Lens colour	Orange
Light type	Strobe
Light source	Xenon
Housing Colour	Black RAL 9005

RATED OPERATING CONDITIONS

Nominal Supply Voltage	230-240 V AC
Nominal current	100 mA
Flash energy	5 J
Flash frequency	1 Hz
Operational temperature	-30°C ... 50°C
Terminal connection	2,5 mm ²

DIMENSIONS

Height	102 mm
Diameter	120 mm

ADDITIONAL DATA

IP class	IP65
----------	------

