

FPM-7211W-P3AE 21.5" Industrial Monitor, Touchscreen, Direct-VGA and DVI



- 10-fingers multitouch
- SECC Chassis with IP66 in front
- 16:9 Wide screen format
- 21,5"
- Panel mounted or welded



## PRODUCT DESCRIPTION

The FPM-7000 Series is the most robust and industry-class screen in our range. With a full-length glass on the front, this monitor becomes IP66 classed and robust, which means that the frame does not feel and creates a significantly better overall impression than other series and models on the market.

With viewing angles and high brightness, this monitor is suitable for all types of applications

## **TECHNICAL DATA**

Approvals	CCC, CE, FCC, UL, BSMI
Backlight	LED LCD
Contrast	5000:1
Depth	47,7 mm
Display format	16:9
Display resolution	1920x1080
Display size	21,5 "
Front panel thickness	7 mm
Height	349,8 mm
Hole size	550,3x341,8
IP class	IP66
Luminance	300 cd/m <sup>2</sup>
Material front frame	Aluminium

Material protection	Zinc plated steel
Number of display colours	16,7
Power consumption	25 W
Power supply	24 V DC
Storage temperature max	60 °C
Storage temperature min	-20 °C
Temperature operational max	55 °C
Temperature operational min	0 °C
Weight	8 kg
Width	558,4 mm
Viewing angle	178/178

