VALCO - LEVEL SWITCH, SIDE MOUNT - B77 SERIES

00.0002.6735 Adj. length, Elbow rod, Brass/SS/ABS, 1xCO, Max 10 bar

- PP housing with PG9 electrical connection
- Micro-switch SPDT
- Max working pressure 20 bar
- Max working temperature 120°C
- Process connection Brass or St. Steel materials





PRODUCT DESCRIPTION

These level switches, with their reduced dimensions and simplicity of installation, constitute a reliable solution for the control of liquids in all applications where it is necessary to mount a lateral type. Suitable for use with process temperatures up to 120 ° C

TECHNICAL DATA

Current	3A
Electrical connection	PG9 cable gland
Function	Changeover (SPDT)
Hysteresis max	24 mm
IP class	IP65
Manufacturer part no.	L1.B77.7.C.25.G.O.W.I33
Material of body	Glass fiber reinforced plastic (PBT)
Material of float	SPANSIL
Material of seals	PTFE
Material of wetted parts	Stainless steel
Mounting	Horizontal
Number of microswitches	1
Pressure max	
riessule illax	10 bar
Process connection	10 bar G1
Process connection	G1
Process connection Rod type	G1 Angled
Process connection Rod type Specific gravity	G1 Angled 0.4





