

## PUSH-IN SOCKETS

S7-PI  
SOCKET QRC 8 PIN DIN RAIL PUSH-IN

- 8 pin S7 and 14 pin S9 relay sockets
- 5 pin S10 and 8 pin S12 relay sockets
- 25% space saving
- Time saving installation



### PRODUCT DESCRIPTION

The New ComatReleco Push-in socket family is now available and offers a compact space saving alternative to screw terminal base.

The range features -

- 25% space saving compared to other brands
- For single wire and stranded wire (un-crimped / crimped)
- Wire cross section range 0.34 mm<sup>2</sup> / AWG 22 to 2.5 mm<sup>2</sup> / AWG 14
- 2 wires per pole
- Snap-in mechanism for 11 mm marking strip
- Tool free mounting and removal from TS35 DIN Rail
- Insertion tool for quick and easy wiring

### TECHNICAL DATA

#### OUTPUT DATA

<b>Breaking Voltage</b>	250 V
<b>Breaking capacity current</b>	10 A

#### GENERAL DATA

<b>Performance</b>	Push-In socket
<b>Isolation connection/connection</b>	2500 V
<b>Isolation connection/rail</b>	2500 V
<b>Material</b>	PA
<b>Connection area multiple conductors</b>	2x0,34-2,5 mm <sup>2</sup>
<b>Temperature operational min</b>	-40 °C

<b>Storage temperature min</b>	-40 °C
<b>Storage temperature max</b>	80 °C
<b>Temperature operational max</b>	60 °C
<b>Weight</b>	46 g

