


INSULATED BOOTLACE FERRULES 0.14MM² TO 4MM²

V30AE001669

0.14mm² x 6mm Ferrule - Brown

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.14...4 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

| | |
|-----------------------------------|----------------------|
| Colour | Brown |
| Cross section max | 0,14 mm ² |
| Rated wire cross section to (AWG) | 26 |
| Standard | French Standard |

DIMENSIONS

| | |
|---------------------|---------|
| Length | 10 mm |
| Length of tube | 6 mm |
| Stripping length | 8 mm |
| Thickness of collar | 0,25 mm |
| Thickness of tube | 0,15 mm |
| Diameter of collar | 1,8 mm |

| | |
|------------------|---------|
| Diameter of tube | 0,85 mm |
|------------------|---------|

MATERIALS

| | |
|----------------------------|----------------------------|
| Conductor tube | Copper alloy |
| Contact surface | Galvanic tin-plated, shiny |
| Plastic collar | Polypropylene-homopolymer |
| Operating temperature from | -5 °C |
| Operating temperature to | 105 °C |

APPROVALS

| | |
|------------------|-----|
| DIN 46228-4:1990 | Yes |
| DIN 46228-1:1992 | No |

ADDITIONAL DATA

| | |
|-------------------|----------|
| Tariff code | 85369010 |
| Country of origin | DE |
| Weight | 0,06 g |
| Pack size | 500 |

