

PR12 CAM SWITCHES

Single-hole mount Ø22,5 mm

PR122203C8EN

PR12 cam switch 16A "1-0-2" 3-pole ø22mm

- Switching current 16A
- Metal Shaft
- Terminal screws in open position
- Special cam switches



PRODUCT DESCRIPTION

TECHNICAL DATA

| | |
|---|------------------------------|
| Angle | 45° |
| Cable size single core max | 4 mm ² |
| Cable size stranded max | 2.5 mm ² |
| Conventional free air thermal current I _{th} | 20 A |
| Function | Stable |
| Mounting | Single hole mounting Ø22.5mm |
| Number of contacts | 6 |
| Number of poles | 3 |
| Plate | 48x48 |
| Positions | 3 |
| Protection rating front of panel | IP40 |
| Protection rating rear of panel | IP20 |
| Rated insulation voltage ac (IEC 60947-1) | 690 V |
| Rated insulation voltage ac (UL 508) | 600 V |
| Rated insulation voltage U _i | 690 V |
| Rated operating current I _e (AC15/230V) | 6 A |

| | |
|--|--|
| Rated operating current Ie (AC21A/22A) | 16 A |
| Rated operating current Ie (DC-1/24 VDC) | 16 A |
| Rated operating power (AC23A/3x230V) | 4 kW |
| Rated operating power (AC23A/3x400V) | 7.5 kW |
| Rated operating power (AC23A/3x500V) | 5.5 kW |
| Rated operating power (AC23A/3x690V) | 4 kW |
| Rated operating power (AC3/3x230V) | 3 kW |
| Rated operating power (AC3/3x400V) | 4 kW |
| Rated operating power (AC3/3x500V) | 5.5 kW |
| Rated operating power (AC3/3x690V) | 3 kW |
| Standards | BV, CB, CCC, CE, CSA, IEC 60947-3, IEC 60947-1, UL, UL 508 |
| Temperature operational max | 70 °C |
| Temperature operational min | -20 °C |
| Type | Changeover switch |

