OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

PR12 CAM SWITCHES

Single-hole mount Ø22,5 mm

PR128357C8EN
PR12 voltmeter switch 16A ø22mm



- Switching current 16A
- Metal Shaft
- Terminal screws in open position
- Special cam switches

PRODUCT DESCRIPTION

TECHNICAL DATA

Type	Voltmeter switch
Mounting	Single hole mounting Ø22.5mm
1333_Plate (mm)	48x48
Number of poles	1
Number of contacts	6
Positions	7
Angle	45°
Function	Stable

Rated operating current Ie (AC15/230V)	6 A
Rated operating current Ie (AC21A/22A)	16 A
Rated operating current Ie (DC-1/24 VDC)	16 A

Rated operating power (AC23A/3x230V)	4 kW
Rated operating power (AC23A/3x400V)	7.5 kW
Rated operating power (AC23A/3x500V)	5.5 kW
Rated operating power (AC23A/3x690V)	4 kW
Rated operating power (AC3/3x230V)	3 kW

Rated operating power (AC3/3x400V)	4 kW
Rated operating power (AC3/3x500V)	5.5 kW
Rated operating power (AC3/3x690V)	3 kW

Conventional free air thermal current Ith	20 A
Rated insulation voltage Ui	690 V
Rated insulation voltage ac (IEC 60947-1)	690 V
Rated insulation voltage ac (UL 508)	600 V

Protection rating front of panel	IP40
Protection rating rear of panel	IP20
Cable size stranded max	2.5 mm²
Cable size single core max	4 mm²
Temperature operational min	-20 °C
Temperature operational max	70 °C
Standards	BV, CB, CCC, CE, CSA, IEC 60947-3 , IEC 60947-1, UL, UL 508

