

**AVENTICS AS2-FLS FILTER**

AS2-R412006000

AS2-FLS, G 1/4, 1.5 ... 16 bar, 2100 l/min, semi-automatic

- G1/4" or G3/8"
- Filter Porosity 5 µm
- Suitable for ATEX
- Fully and semi-automatic

**PRODUCT DESCRIPTION**

Filters are used to remove solid and liquid contaminants e.g. dust particles and condensed water in compressed air. Good filtration prevents malfunctions and component wear is minimized. Filters are most often used in combination with other air treatment components.

**TECHNICAL DATA**

<b>Bowl volume</b>	16 cm <sup>3</sup>
<b>Connection air</b>	G1/4
<b>Drain connection</b>	G1/8"
<b>Filter element</b>	5 µm
<b>Function</b>	Particle filter
<b>Manometer</b>	No
<b>Material bowl</b>	Polycarbonate
<b>Material of seals</b>	NBR
<b>Material protection</b>	Polyamide
<b>Media</b>	Air pressure
<b>Nominal flow</b>	2100 l/min
<b>Operating pressure max</b>	12 bar
<b>Operating pressure min</b>	1.5 bar
<b>Temperature operational max</b>	50 °C
<b>Temperature operational min</b>	-10 °C

Weight

0.212 kg

