OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INSULATED SPADE TERMINALS

FSH

2558.0
FST 1/6.3 1.5mm², 6.3 x 0.8mm insulated male spade crimp, Red



- Brass (CuZn), metalic insulation holder Cu-ETP, galv, Sn
- Wide easy entry collar PVC insulation
- Continuous-use temperature range -10°C…75°C
- Male, female and piggy back options

PRODUCT DESCRIPTION

Conta-Clip offer a range of standard automotive type insulated spade crimp terminals to suit many applications.

These terminals are usually identified by the coloured collars for the various cable sizes.

The standard range covers from 0.5mm² to 6mm² cable sizes with 2.8mm to 6.3mm faston connections. These are also available as fully insulated or 'piggy back' variants.

All types within the range have a widened cable entry, making for an easy installation.

TECHNICAL DATA

GENERAL DATA

Colour	Red
Cross section min	0.5 mm²
Cross section max	1.5 mm²
Rated wire cross section from (AWG)	20
Rated wire cross section to (AWG)	16

DIMENSIONS

Length	21.5 mm
Diameter of feed-in funnel	3.5 mm

MATERIALS

Conductor material	Copper

Contact surface	Tinned
Soldered	No
Operating temperature from	-10 °C
Operating temperature to	75 °C

ADDITIONAL DATA

Tariff code	85369010
Country of origin	TW
Weight	0.93 g
Pack size	100

Insulation material	Expanded PVC

