OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INSULATED RING TERMINALS

QKS

2541.0
QKS 6, 6mm² Ring crimp, M4, Yellow



- Ring shape complies with DIN 46237
- Cu-ETP acc. to DIN EN13599, soldered,galv, Sn
- Wide easy entry collar PA insulation
- Continuous-use temperature range -55°C…105°C

PRODUCT DESCRIPTION

Conta-Clip offer a range of standard automotive type insulated ring crimp terminals to suit many applications.

These terminals are usually identified by the coloured collars for the various cable sizes.

The standard range covers from 0.5mm² to 6mm² cable sizes with M4 to M8 connections.

All types within the range have a widened cable entry, making for an easy installation.

TECHNICAL DATA

GENERAL DATA

Colour	Yellow
Cross section min	4 mm²
Cross section max	6 mm²
Ring hole diameter	4.3 mm
Conductor shape	Ring shape acc.DIN 46237
Rated wire cross section from (AWG)	12
Rated wire cross section to (AWG)	10

DIMENSIONS

Width of ring	8 mm
Length to middle of ring	21 mm

Diameter of feed-in funnel	6.5 mm
DIN size	A 4 - 6

MATERIALS

Conductor material	Copper
Contact surface	Tinned
Soldered	Yes
Operating temperature from	-55 °C
Operating temperature to	105 °C

APPROVALS

DIN approvals	EN 13599

ADDITIONAL DATA

Tariff code	85369010
Country of origin	TW
Weight	1.73 g
Pack size	100

Insulation material	Expanded PA

