

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INSULATED FORK TERMINALS

QKS G

3066.0 QKS G 1, 1mm² Fork crimp, M6, Red

- Fork shaped acc. to DIN 46237/C
- Cu-ETP acc. to DIN EN13599, soldered, galc, Sn
- Wide easy entry collar PA insulation
- Continuous-use temperature range -55°C...105°C



ZCONTACLIP

PRODUCT DESCRIPTION

Conta-Clip offer a range of standard automotive type insulated fork crimp terminals to suit many applications.

These terminals are usually identified by the coloured collars for the various cable sizes.

The standard range covers from 0.5mm² to 6mm² cable sizes with M4 to M8 connections.

All types within the range have a widened cable entry, making for an easy installation.

TECHNICAL DATA

GENERAL DATA

| Colour | Red |
|-------------------------------------|-----------------------------|
| Cross section min | 0.5 mm² |
| Cross section max | 1 mm² |
| Conductor shape | Fork shape acc. DIN 46237/C |
| Rated wire cross section from (AWG) | 20 |
| Rated wire cross section to (AWG) | 18 |
| DIMENSIONS | |
| Diameter of feed-in funnel | 4.1 mm |
| DIN size | C 6 - 1 |

MATERIALS

| Conductor material | Copper |
|----------------------------|-------------|
| Contact surface | Tinned |
| Soldered | Yes |
| Operating temperature from | -55 °C |
| Operating temperature to | 105 °C |
| APPROVALS | |
| DIN approvals | EN 13599 |
| ADDITIONAL DATA | |
| Tariff code | 85369010 |
| Country of origin | TW |
| Weight | 1.2 g |
| Pack size | 100 |
| Insulation material | Expanded PA |

