

INSULATED BUTT TERMINALS

STV, STV HS

3075.0

STV 2.5, 2.5mm² Insulated joint/butt crimp, Blue

- Cu-ETP acc. to DIN EN13600, galv, Sn
- Wide easy entry collars PVC insulation
- Continuous-use temperature range -10°C...75°C
- Heat shrink waterproof versions



PRODUCT DESCRIPTION

Conta-Clip offer a range of standard automotive type insulated joining/butt crimp terminals to suit many applications.

These terminals are usually identified by the coloured collars for the various cable sizes.

The standard range covers from 0.5mm² to 6mm² cable sizes.

All types within the range have a widened cable entry, making for an easy installation.

The HS versions have a double layer of insulation and combined adhesive heat shrink to give a waterproof joint for the harshest applications.

TECHNICAL DATA

GENERAL DATA

| | |
|-------------------------------------|---------------------|
| Colour | Blue |
| Cross section min | 1.5 mm ² |
| Cross section max | 2.5 mm ² |
| Rated wire cross section from (AWG) | 16 |
| Rated wire cross section to (AWG) | 14 |

DIMENSIONS

| | |
|----------------------------|--------|
| Length | 26 mm |
| Diameter of feed-in funnel | 4.5 mm |

| | |
|----------|-----|
| DIN size | 2.5 |
|----------|-----|

MATERIALS

| | |
|----------------------------|--------|
| Conductor material | Copper |
| Contact surface | Tinned |
| Soldered | No |
| Operating temperature from | -10 °C |
| Operating temperature to | 75 °C |

APPROVALS

| | |
|---------------|----------|
| DIN approvals | EN 13600 |
|---------------|----------|

ADDITIONAL DATA

| | |
|---------------------|--------------|
| Tariff code | 85369010 |
| Country of origin | TW |
| Weight | 1.4 g |
| Pack size | 100 |
| Insulation material | Expanded PVC |



