

## INSULATED BUTT TERMINALS

STV, STV HS

3076.0

STV 6, 2.5mm<sup>2</sup> Insulated joint/butt crimp, Blue

- Cu-ETP acc. to DIN EN13600, galv, Sn
- Wide easy entry collars PVC insulation
- Continuous-use temperature range -10°C...75°C
- Heat shrink waterproof versions



### PRODUCT DESCRIPTION

Conta-Clip offer a range of standard automotive type insulated joining/butt crimp terminals to suit many applications.

These terminals are usually identified by the coloured collars for the various cable sizes.

The standard range covers from 0.5mm<sup>2</sup> to 6mm<sup>2</sup> cable sizes.

All types within the range have a widened cable entry, making for an easy installation.

The HS versions have a double layer of insulation and combined adhesive heat shrink to give a waterproof joint for the harshest applications.

## TECHNICAL DATA

### GENERAL DATA

Colour	Yellow
Cross section min	4 mm <sup>2</sup>
Cross section max	6 mm <sup>2</sup>
Rated wire cross section from (AWG)	12
Rated wire cross section to (AWG)	10

### DIMENSIONS

Length	27 mm
Diameter of feed-in funnel	6.5 mm

DIN size	6
----------	---

### MATERIALS

Conductor material	Copper
Contact surface	Tinned
Soldered	No
Operating temperature from	-10 °C
Operating temperature to	75 °C

### APPROVALS

DIN approvals	EN 13600
---------------	----------

### ADDITIONAL DATA

Tariff code	85369010
Country of origin	TW
Weight	2.34 g
Pack size	100
Insulation material	Expanded PVC



