

## UNINSULATED TUBE CABLE LUGS - RKS

30959.0

RKS 120/U/M8, 120mm<sup>2</sup> Seamless cable lug, M8

- Heat resistant up to 125 °C
- Cu-ETP, DIN EN13600
- Size range 6 mm<sup>2</sup>...630mm<sup>2</sup>
- Tubed version



### PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The RKS tube cable lugs start a 6 mm<sup>2</sup> through 630 mm<sup>2</sup> (M4/M20) and also have 90° angled versions for compact spaces.

To complete the range, a selection of un-insulated SKS pin crimp and STV butt connectors are also available.

## TECHNICAL DATA

### GENERAL DATA

Colour	Natural
Cross section max	120 mm <sup>2</sup>
Metric connecting thread size	M 8
Conductor shape	Ring shape
Rated wire cross section to (AWG)	250

### DIMENSIONS

Width of ring	28 mm
Length to middle of ring	51 mm
Length of feed-in funnel	26 mm
Diameter of feed-in funnel	15 mm
Stripping length	26 mm

MATERIALS

Conductor material	Copper
Contact surface	Tinned
Soldered	No
Operating temperature to	125 °C

APPROVALS

DIN approvals	EN 13600
---------------	----------

ADDITIONAL DATA

Tariff code	85369010
Country of origin	TW
Weight	67.05 g
Pack size	50

