

UNINSULATED TUBE CABLE LUGS - RKS

30953.0

RKS 95/U/M8, 95mm² Seamless cable lug, M8

- Heat resistant up to 125 °C
- Cu-ETP, DIN EN13600
- Size range 6 mm²...630mm²
- Tubed version



PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The RKS tube cable lugs start a 6 mm² through 630 mm² (M4/M20) and also have 90° angled versions for compact spaces.

To complete the range, a selection of un-insulated SKS pin crimp and STV butt connectors are also available.

TECHNICAL DATA

GENERAL DATA

Colour	Natural
Cross section max	95 mm ²
Metric connecting thread size	M 8
Ring hole diameter	8.4 mm
Conductor shape	Ring shape
Rated wire cross section to (AWG)	3/0

DIMENSIONS

Width of ring	26 mm
Length to middle of ring	48 mm
Length of feed-in funnel	25 mm
Diameter of feed-in funnel	13.5 mm

Stripping length	25 mm
------------------	-------

MATERIALS

Conductor material	Copper
--------------------	--------

Contact surface	Tinned
-----------------	--------

Soldered	No
----------	----

Operating temperature to	125 °C
--------------------------	--------

APPROVALS

DIN approvals	EN 13600
---------------	----------

ADDITIONAL DATA

Tariff code	85369010
-------------	----------

Country of origin	TW
-------------------	----

Weight	56.35 g
--------	---------

Pack size	50
-----------	----

