

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk



UNINSULATED RING SHAPED LUGS – QKS

QKS

30822.0 QKS 6/U/M10, 6mm² Seamed cable lug, M10

- Heat resistant up to 125 °C
- Soldered; DIN EN13599
- Size range 0.5 mm²...240 mm²
- · Seamed version



PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The galvanised QKS seamed ring shaped lugs start at 0.5mm² through 240mm² (M2.5/M16).

To complete the range, a selection of un-insulated SKS pin crimp and STV butt connectors are also available.

TECHNICAL DATA

GENERAL DATA

| Colour | Natural |
|-------------------------------------|--------------------------|
| Cross section min | 2.5 mm² |
| Cross section max | 6 mm² |
| Metric connecting thread size | M 10 |
| Ring hole diameter | 10.5 mm |
| Conductor shape | Ring shape acc.DIN 46234 |
| Rated wire cross section from (AWG) | 14 |
| Rated wire cross section to (AWG) | 10 |

DIMENSIONS

| Width of ring | 18 mm |
|--------------------------|-------|
| Length to middle of ring | 21 mm |
| Length of feed-in funnel | 6 mm |

| Diameter of feed-in funnel | 3.6 mm |
|----------------------------|--------|
| Stripping length | 6 mm |

MATERIALS

| Conductor material | Copper |
|--------------------------|--------|
| Contact surface | Tinned |
| Soldered | Yes |
| Operating temperature to | 125 °C |

APPROVALS

| DIN approvals EN 13599 | |
|------------------------|--|
|------------------------|--|

ADDITIONAL DATA

| Tariff code | 85369010 |
|-------------------|----------|
| Country of origin | TW |
| Weight | 2.95 g |
| Pack size | 50 |

