

# *<b>ZCONTACLIP*

## **UNINSULATED RING SHAPED LUGS –** QKS QKS

30854.0 QKS 70/U/M8, 70mm<sup>2</sup> Seamed cable lug, M8

- Heat resistant up to 125 °C
- Soldered; DIN EN13599
- Size range 0.5 mm<sup>2</sup>...240 mm<sup>2</sup>
- · Seamed version



#### PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The galvanised QKS seamed ring shaped lugs start at 0.5mm<sup>2</sup> through 240mm<sup>2</sup> (M2.5/M16). To complete the range, a selection of un-insulated SKS pin crimp and STV butt connectors are also available.

## **TECHNICAL DATA**

#### **GENERAL DATA**

Colour	Natural
Cross section max	70 mm²
Metric connecting thread size	M 8
Ring hole diameter	8.4 mm
Conductor shape	Ring shape acc.DIN 46234
Rated wire cross section to (AWG)	2/0

#### DIMENSIONS

Width of ring	22 mm
Length to middle of ring	38 mm
Length of feed-in funnel	18 mm
Diameter of feed-in funnel	13 mm
Stripping length	18 mm

### MATERIALS

Conductor material	Copper
Contact surface	Tinned
Soldered	Yes
Operating temperature to	125 °C

### APPROVALS

DIN approvals	EN 13599
---------------	----------

## ADDITIONAL DATA

Tariff code	85369010
Country of origin	TW
Weight	25.1 g
Pack size	25

