OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

UNINSULATED TUBE CABLE LUGS - RKS

30940.0
RKS 50/U/M8, 50mm² Seamless cable lug, M8



- Heat resistant up to 125 °C
- Cu-ETP, DIN EN13600
- Size range 6 mm²…630mm²
- Tubed version

PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The RKS tube cable lugs start a 6 mm² through 630 mm² (M4/M20) and also have 90° angled versions for compact spaces.

To complete the range, a selection of un-insulated SKS pin crimp and STV butt connectors are also available.

TECHNICAL DATA

GENERAL DATA

Colour	Natural
Cross section max	50 mm²
Metric connecting thread size	M 8
Ring hole diameter	8.4 mm
Conductor shape	Ring shape
Rated wire cross section to (AWG)	1/0

DIMENSIONS

Width of ring	20 mm
Length to middle of ring	37 mm
Length of feed-in funnel	19 mm
Diameter of feed-in funnel	10 mm
Stripping length	19 mm

MATERIALS

Conductor material	Copper
Contact surface	Tinned
Soldered	No
Operating temperature to	125 °C

APPROVALS

DIN approvals	EN 13600

ADDITIONAL DATA

Tariff code	85369010
Country of origin	PL
Weight	29.33 g
Pack size	100

