

INSULATED BUTT TERMINALS

STV, STV HS

30800.0

STV 0.5/HS, 0.5mm² double layer insulated joint/butt crimp with combined heat shrink - White

- Cu-ETP acc. to DIN EN13600, galv, Sn
- Wide easy entry collars PVC insulation
- Continuous-use temperature range -10°C...75°C
- Heat shrink waterproof versions



PRODUCT DESCRIPTION

Conta-Clip offer a range of standard automotive type insulated joining/butt crimp terminals to suit many applications.

These terminals are usually identified by the coloured collars for the various cable sizes.

The standard range covers from 0.5mm² to 6mm² cable sizes.

All types within the range have a widened cable entry, making for an easy installation.

The HS versions have a double layer of insulation and combined adhesive heat shrink to give a waterproof joint for the harshest applications.

TECHNICAL DATA

GENERAL DATA

Colour	White
Cross section min	0.1 mm ²
Cross section max	0.5 mm ²
Rated wire cross section from (AWG)	36
Rated wire cross section to (AWG)	20

DIMENSIONS

Length	35 mm
Diameter of feed-in funnel	4.3 mm

MATERIALS

Conductor material	Copper
Contact surface	Tinned
Soldered	No

APPROVALS

DIN approvals	EN 13600
---------------	----------

ADDITIONAL DATA

Tariff code	85369010
Country of origin	TW
Weight	1.31 g
Pack size	100
Insulation material	thermoplastic

