OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

INSULATED BUTT TERMINALS

STV, STV HS

30802.0
STV 2,5/HS, 2.5mm² double layer insulated joint/butt crimp with combined heat shrink - Blue



- Cu-ETP acc. to DIN EN13600, galv, Sn
- Wide easy entry collars PVC insulation
- Continuous-use temperature range -10°C…75°C
- Heat shrink waterproof versions

PRODUCT DESCRIPTION

Conta-Clip offer a range of standard automotive type insulated joining/butt crimp terminals to suit many applications.

These terminals are usually identified by the coloured collars for the various cable sizes.

The standard range covers from 0.5mm² to 6mm² cable sizes.

All types within the range have a widened cable entry, making for an easy installation.

The HS versions have a double layer of insulation and combined adhesive heat shrink to give a waterproof joint for the harshest applications.

TECHNICAL DATA

GENERAL DATA

Colour	Blue
Cross section min	1.5 mm²
Cross section max	2.5 mm²
Rated wire cross section from (AWG)	16
Rated wire cross section to (AWG)	14

DIMENSIONS

Length	35 mm
Diameter of feed-in funnel	5 mm

MATERIALS

Conductor material	Copper
Contact surface	Tinned
Soldered	No

APPROVALS

DIN approvals	EN 13600

ADDITIONAL DATA

Tariff code	85369010
Country of origin	TW
Weight	1.58 g
Pack size	100

Insulation material	thermoplastic





