OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# UNINSULATED RING SHAPED LUGS – QKS

QKS

30811.0
QKS 2,5/U/M3, 2.5mm² Seamed cable lug, M3



- Heat resistant up to 125 °C
- Soldered; DIN EN13599
- Size range 0.5 mm²…240 mm²
- Seamed version

### PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The galvanised QKS seamed ring shaped lugs start at 0.5mm² through 240mm² (M2.5/M16).
To complete the range, a selection of un-insulated SKS pin crimp and STV butt connectors are also available.

# TECHNICAL DATA

## GENERAL DATA

| | |
|---|---|
| **Colour** | Natural |
| **Cross section min** | 1.5 mm² |
| **Cross section max** | 2.5 mm² |
| **Metric connecting thread size** | M 3 |
| **Ring hole diameter** | 3.2 mm |
| **Conductor shape** | Ring shape acc.DIN 46234 |
| **Rated wire cross section from (AWG)** | 16 |
| **Rated wire cross section to (AWG)** | 14 |

## DIMENSIONS

| | |
|---|---|
| **Width of ring** | 6 mm |
| **Length to middle of ring** | 10.8 mm |
| **Length of feed-in funnel** | 4.8 mm |
| **Diameter of feed-in funnel** | 2.3 mm |

| | |
|---|---|
| **Stripping length** | 4.8 mm |

## MATERIALS

| | |
|---|---|
| **Conductor material** | Copper |
| **Contact surface** | Tinned |
| **Soldered** | Yes |
| **Operating temperature to** | 125 °C |

## APPROVALS

| | |
|---|---|
| **DIN approvals** | EN 13599 |

## ADDITIONAL DATA

| | |
|---|---|
| **Tariff code** | 85369010 |
| **Country of origin** | TW |
| **Weight** | 0.68 g |
| **Pack size** | 100 |

