OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

UNINSULATED RING SHAPED LUGS – QKS

QKS

30817.0
QKS 2,5/U/M10, 2.5mm² Seamed cable lug, M10



- Heat resistant up to 125 °C
- Soldered; DIN EN13599
- Size range 0.5 mm²…240 mm²
- Seamed version

PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The galvanised QKS seamed ring shaped lugs start at 0.5mm² through 240mm² (M2.5/M16).
To complete the range, a selection of un-insulated SKS pin crimp and STV butt connectors are also available.

TECHNICAL DATA

GENERAL DATA

Colour	Natural
Cross section min	1.5 mm²
Cross section max	2.5 mm²
Metric connecting thread size	M 10
Ring hole diameter	10.5 mm
Conductor shape	Ring shape acc.DIN 46234
Rated wire cross section from (AWG)	16
Rated wire cross section to (AWG)	14

DIMENSIONS

Width of ring	15 mm
Length to middle of ring	17 mm
Length of feed-in funnel	4.8 mm
Diameter of feed-in funnel	2.3 mm

Stripping length	4.8 mm

MATERIALS

Conductor material	Copper
Contact surface	Tinned
Soldered	Yes
Operating temperature to	125 °C

APPROVALS

DIN approvals	EN 13599

ADDITIONAL DATA

Tariff code	85369010
Country of origin	TW
Weight	1.59 g
Pack size	100

