OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

UNINSULATED RING SHAPED LUGS – QKS

QKS

30853.0
QKS 70/U/M6, 70mm² Seamed cable lug, M6



- Heat resistant up to 125 °C
- Soldered; DIN EN13599
- Size range 0.5 mm²…240 mm²
- Seamed version

PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The galvanised QKS seamed ring shaped lugs start at 0.5mm² through 240mm² (M2.5/M16).
To complete the range, a selection of un-insulated SKS pin crimp and STV butt connectors are also available.

TECHNICAL DATA

GENERAL DATA

Colour	Natural
Cross section max	70 mm²
Metric connecting thread size	M 6
Ring hole diameter	6.5 mm
Conductor shape	Ring shape acc.DIN 46234
Rated wire cross section to (AWG)	2/0

DIMENSIONS

Width of ring	22 mm
Length to middle of ring	38 mm
Length of feed-in funnel	18 mm
Diameter of feed-in funnel	13 mm
Stripping length	18 mm

MATERIALS

Conductor material	Copper
Contact surface	Tinned
Soldered	Yes
Operating temperature to	125 °C

APPROVALS

DIN approvals	EN 13599

ADDITIONAL DATA

Tariff code	85369010
Country of origin	TW
Weight	27.1 g
Pack size	25

