

UNINSULATED RING SHAPED LUGS – QKS

QKS

30860.0

QKS 95/U/M10, 95mm² Seamed cable lug, M10

- Heat resistant up to 125 °C
- Soldered; DIN EN13599
- Size range 0.5 mm²...240 mm²
- Seamed version



PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The galvanised QKS seamed ring shaped lugs start at 0.5mm² through 240mm² (M2.5/M16).

To complete the range, a selection of un-insulated SKS pin crimp and STV butt connectors are also available.

TECHNICAL DATA

GENERAL DATA

Colour	Natural
Cross section max	95 mm ²
Metric connecting thread size	M 10
Ring hole diameter	10.5 mm
Conductor shape	Ring shape acc.DIN 46234
Rated wire cross section to (AWG)	3/0

DIMENSIONS

Width of ring	24 mm
Length to middle of ring	42 mm
Length of feed-in funnel	20 mm
Diameter of feed-in funnel	15 mm
Stripping length	20 mm

MATERIALS

Conductor material	Copper
Contact surface	Tinned
Soldered	Yes
Operating temperature to	125 °C

APPROVALS

DIN approvals	EN 13599
---------------	----------

ADDITIONAL DATA

Tariff code	85369010
Country of origin	TW
Weight	41.1 g
Pack size	25

