

## UNINSULATED RING SHAPED LUGS – QKS

QKS

30868.0

QKS 120/U/M16, 120mm<sup>2</sup> Seamed cable lug, M16

- Heat resistant up to 125 °C
- Soldered; DIN EN13599
- Size range 0.5 mm<sup>2</sup>...240 mm<sup>2</sup>
- Seamed version



## PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The galvanised QKS seamed ring shaped lugs start at 0.5mm<sup>2</sup> through 240mm<sup>2</sup> (M2.5/M16).

To complete the range, a selection of un-insulated SKS pin crimp and STV butt connectors are also available.

## TECHNICAL DATA

## GENERAL DATA

|                                   |                          |
|-----------------------------------|--------------------------|
| Colour                            | Natural                  |
| Cross section max                 | 120 mm²                  |
| Metric connecting thread size     | M 16                     |
| Ring hole diameter                | 17 mm                    |
| Conductor shape                   | Ring shape acc.DIN 46234 |
| Rated wire cross section to (AWG) | 250                      |

## DIMENSIONS

|                            |         |
|----------------------------|---------|
| Width of ring              | 28 mm   |
| Length to middle of ring   | 48 mm   |
| Length of feed-in funnel   | 22 mm   |
| Diameter of feed-in funnel | 16.5 mm |
| Stripping length           | 22 mm   |

MATERIALS

|                          |        |
|--------------------------|--------|
| Conductor material       | Copper |
| Contact surface          | Tinned |
| Soldered                 | Yes    |
| Operating temperature to | 125 °C |

APPROVALS

|               |          |
|---------------|----------|
| DIN approvals | EN 13599 |
|---------------|----------|

ADDITIONAL DATA

|                   |          |
|-------------------|----------|
| Tariff code       | 85369010 |
| Country of origin | TW       |
| Weight            | 58.1 g   |
| Pack size         | 25       |

