

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **UNINSULATED BUTT CONNECTORS -**STV

STV

30895.0 STV 4/U, 4mm<sup>2</sup> joint connector

- Joint connectors for cables from 0.5 mm<sup>2</sup> to 300 mm<sup>2</sup>
- Cu-ETP acc. to EN 13600, galv. Sn
- Heat resistant to +125 °C



**ZCONTACLIP** 

## PRODUCT DESCRIPTION

Conta-Clip offer a wide range of conventional uninsulated tin-plated copper, galvanised cable joining butt connectors.

These conform to EN 136000 with an operating temperature of up to 125°C and are available from 1mm<sup>2</sup> to 300mm<sup>2</sup>.

## **TECHNICAL DATA**

## **GENERAL DATA**

Colour	Natural
Cross section min	4 mm <sup>2</sup>
Cross section max	6 mm²
Rated wire cross section from (AWG)	12
Rated wire cross section to (AWG)	10
DIMENSIONS	
Length	14.5 mm
Stripping length	7 mm
MATERIALS	
Conductor material	Copper
Contact surface	Tinned
Soldered	No

Operating temperature to	125 °C
APPROVALS	
DIN approvals	EN 13600
ADDITIONAL DATA	
Tariff code	85369010
Country of origin	TW
Weight	2.41 g
Pack size	100



