

UNINSULATED TUBE CABLE LUGS - RKS

30913.0

RKS 6/U/M8, 6mm² Seamless cable lug, M8

- Heat resistant up to 125 °C
- Cu-ETP, DIN EN13600
- Size range 6 mm²...630mm²
- Tubed version



PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The RKS tube cable lugs start a 6 mm² through 630 mm² (M4/M20) and also have 90° angled versions for compact spaces.

To complete the range, a selection of un-insulated SKS pin crimp and STV butt connectors are also available.

TECHNICAL DATA

GENERAL DATA

| | |
|-----------------------------------|-------------------|
| Colour | Natural |
| Cross section max | 6 mm ² |
| Metric connecting thread size | M 8 |
| Ring hole diameter | 8.4 mm |
| Conductor shape | Ring shape |
| Rated wire cross section to (AWG) | 10 |

DIMENSIONS

| | |
|----------------------------|--------|
| Width of ring | 15 mm |
| Length to middle of ring | 23 mm |
| Length of feed-in funnel | 9.5 mm |
| Diameter of feed-in funnel | 3.5 mm |

| | |
|------------------|--------|
| Stripping length | 9.5 mm |
|------------------|--------|

MATERIALS

| | |
|--------------------------|--------|
| Conductor material | Copper |
| Contact surface | Tinned |
| Soldered | No |
| Operating temperature to | 125 °C |

APPROVALS

| | |
|---------------|----------|
| DIN approvals | EN 13600 |
|---------------|----------|

ADDITIONAL DATA

| | |
|-------------------|----------|
| Tariff code | 85369010 |
| Country of origin | TW |
| Weight | 6.13 g |
| Pack size | 100 |

