

UNINSULATED TUBE CABLE LUGS - RKS

30915.0

RKS 6/U/M12, 6mm² Seamless cable lug, M12

- Heat resistant up to 125 °C
- Cu-ETP, DIN EN13600
- Size range 6 mm²...630mm²
- Tubed version



PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The RKS tube cable lugs start a 6 mm² through 630 mm² (M4/M20) and also have 90° angled versions for compact spaces.

To complete the range, a selection of un-insulated SKS pin crimp and STV butt connectors are also available.

TECHNICAL DATA

GENERAL DATA

Colour	Natural
Cross section max	6 mm ²
Metric connecting thread size	M 12
Ring hole diameter	13.2 mm
Conductor shape	Ring shape
Rated wire cross section to (AWG)	10

DIMENSIONS

Width of ring	19 mm
Length to middle of ring	28 mm
Length of feed-in funnel	9.5 mm
Diameter of feed-in funnel	3.5 mm

Stripping length	9.5 mm
------------------	--------

MATERIALS

Conductor material	Copper
Contact surface	Tinned
Soldered	No
Operating temperature to	125 °C

APPROVALS

DIN approvals	EN 13600
---------------	----------

ADDITIONAL DATA

Tariff code	85369010
Country of origin	TW
Weight	7.03 g
Pack size	100

