

## UNINSULATED TUBE CABLE LUGS - RKS

30977.0

RKS 240/U/M12, 240mm<sup>2</sup> Seamless cable lug, M12

- Heat resistant up to 125 °C
- Cu-ETP, DIN EN13600
- Size range 6 mm<sup>2</sup>...630mm<sup>2</sup>
- Tubed version



### PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The RKS tube cable lugs start a 6 mm<sup>2</sup> through 630 mm<sup>2</sup> (M4/M20) and also have 90° angled versions for compact spaces.

To complete the range, a selection of un-insulated SKS pin crimp and STV butt connectors are also available.

## TECHNICAL DATA

### GENERAL DATA

|                                   |                     |
|-----------------------------------|---------------------|
| Colour                            | Natural             |
| Cross section max                 | 240 mm <sup>2</sup> |
| Metric connecting thread size     | M 12                |
| Conductor shape                   | Ring shape          |
| Rated wire cross section to (AWG) | 500                 |

### DIMENSIONS

|                            |         |
|----------------------------|---------|
| Width of ring              | 39 mm   |
| Length to middle of ring   | 72 mm   |
| Length of feed-in funnel   | 35 mm   |
| Diameter of feed-in funnel | 21.2 mm |
| Stripping length           | 35 mm   |

MATERIALS

|                          |        |
|--------------------------|--------|
| Conductor material       | Copper |
| Contact surface          | Tinned |
| Soldered                 | No     |
| Operating temperature to | 125 °C |

APPROVALS

|               |          |
|---------------|----------|
| DIN approvals | EN 13600 |
|---------------|----------|

ADDITIONAL DATA

|                   |          |
|-------------------|----------|
| Tariff code       | 85369010 |
| Country of origin | PL       |
| Weight            | 167.75 g |
| Pack size         | 50       |

