

UNINSULATED TUBE CABLE LUGS - RKS

30979.0

RKS 240/U/M16, 240mm² Seamless cable lug, M16

- Heat resistant up to 125 °C
- Cu-ETP, DIN EN13600
- Size range 6 mm²...630mm²
- Tubed version



PRODUCT DESCRIPTION

Conta-Clip continues to add to their portfolio with the addition of un-insulated lug terminals to complement their extensive range of stud terminals.

The RKS tube cable lugs start a 6 mm² through 630 mm² (M4/M20) and also have 90° angled versions for compact spaces.

To complete the range, a selection of un-insulated SKS pin crimp and STV butt connectors are also available.

TECHNICAL DATA

GENERAL DATA

Colour	Natural
Cross section max	240 mm ²
Metric connecting thread size	M 16
Conductor shape	Ring shape
Rated wire cross section to (AWG)	500

DIMENSIONS

Width of ring	39 mm
Length to middle of ring	72 mm
Length of feed-in funnel	35 mm
Diameter of feed-in funnel	21.2 mm
Stripping length	35 mm

MATERIALS

Conductor material	Copper
Contact surface	Tinned
Soldered	No
Operating temperature to	125 °C

APPROVALS

DIN approvals	EN 13600
---------------	----------

ADDITIONAL DATA

Tariff code	85369010
Country of origin	TW
Weight	163.25 g
Pack size	50

