

## TUBULAR CABLE LUGS L SERIES

### 0.75MM<sup>2</sup> - 50MM<sup>2</sup>

L65FMS

6mm<sup>2</sup> Cable Lug M5 Flared

- Simple and safe connection due to flat contact surfaces and internal chamfer
- Reliable assignment owed to item designation on the cable lug
- Ideal cable lug for control cabinet construction
- In combination with the EKM 60 ID and EK 30 ID suitable for fine wired conductors
- Tin-plated to protect against corrosion



#### PRODUCT DESCRIPTION

#### TECHNICAL DATA

##### GENERAL DATA

|                       |                   |
|-----------------------|-------------------|
| Connection bolts Ø    | M5                |
| Nominal cross section | 6 mm <sup>2</sup> |

##### DIMENSIONS

|              |        |
|--------------|--------|
| Dimension A  | 9 mm   |
| Dimension B  | 9.5 mm |
| Dimension D2 | 5.3 mm |
| Dimension C1 | 6.5 mm |
| Dimension C2 | 6.5 mm |
| Dimension D1 | 4 mm   |
| Dimension D4 | 6 mm   |
| Dimension L  | 19 mm  |

##### ADDITIONAL DATA

|           |         |
|-----------|---------|
| Pack size | 100     |
| Weight    | 0.32 kg |

