

## TUBULAR CABLE LUGS L SERIES 70MM<sup>2</sup> - 630MM<sup>2</sup>

L706FMS  
 70mm<sup>2</sup> Cable Lug M6 Flared

- Simple and safe connection due to flat contact surfaces and internal chamfer
- Reliable assignment owed to item designation on the cable lug
- Ideal cable lug for control cabinet construction
- In combination with the EKM 60 ID and EK 30 ID suitable for fine wired conductors
- Tin-plated to protect against corrosion



### PRODUCT DESCRIPTION

Discover KLAUKE's L series tubular cable lugs, designed for 70mm<sup>2</sup> - 630mm<sup>2</sup> cables. Enjoy safe connections, clear item designation, and ideal use in control cabinets.

## TECHNICAL DATA

### GENERAL DATA

Connection bolts Ø	M6
Nominal cross section	70 mm <sup>2</sup>

### DIMENSIONS

Dimension A	20 mm
Dimension B	21 mm
Dimension D2	6.5 mm
Dimension C1	10 mm
Dimension C2	6.5 mm
Dimension D1	11.2 mm
Dimension D4	14.5 mm
Dimension L	39 mm

### ADDITIONAL DATA

Pack size	100
-----------	-----

Weight

3 kg

