

## TUBULAR CABLE LUGS L SERIES 70MM<sup>2</sup> - 630MM<sup>2</sup>

L706FMS

70mm<sup>2</sup> Cable Lug M6 Flared

- Simple and safe connection due to flat contact surfaces and internal chamfer
- Reliable assignment owed to item designation on the cable lug
- Ideal cable lug for control cabinet construction
- In combination with the EKM 60 ID and EK 30 ID suitable for fine wired conductors
- Tin-plated to protect against corrosion



### PRODUCT DESCRIPTION

Discover KLAUKE's L series tubular cable lugs, designed for 70mm<sup>2</sup> - 630mm<sup>2</sup> cables. Enjoy safe connections, clear item designation, and ideal use in control cabinets.

## TECHNICAL DATA

### GENERAL DATA

|                       |                    |
|-----------------------|--------------------|
| Connection bolts Ø    | M6                 |
| Nominal cross section | 70 mm <sup>2</sup> |

### DIMENSIONS

|              |         |
|--------------|---------|
| Dimension A  | 20 mm   |
| Dimension B  | 21 mm   |
| Dimension D2 | 6.5 mm  |
| Dimension C1 | 10 mm   |
| Dimension C2 | 6.5 mm  |
| Dimension D1 | 11.2 mm |
| Dimension D4 | 14.5 mm |
| Dimension L  | 39 mm   |

### ADDITIONAL DATA

|           |     |
|-----------|-----|
| Pack size | 100 |
|-----------|-----|

---

Weight

3 kg

---

