

PK 100

10001.1

PK 100/5/2V 2P PCB TERM VERT GREEN

- Supports conductor ranges between 0.14–2.5 mm²
- Current up to 10 A at voltages between 250 V and 630 V
- high insulation resistance



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Type	PCB terminal
Pitch	5 mm
Colour	Green
Number of poles	2
Approvals	UL, cUL, VDE

RATINGS

Rated current	24 A
Rated voltage	250 V
Rated cross section	2.5 mm ²
Rated impulse voltage	2 kV
Overvoltage category	III
Contamination degree	3

DIMENSIONS

Length	9 mm
Width	10.7 mm
Height	12.5 mm
Width left	3.2 mm
Width right	2.5 mm
Drillhole diameter	1.3 mm

Diameter of the connection pin	1 mm
Length of pin	4.5 mm

CONNECTION DATA

Connector type/principle	Wire protection
Number of levels	1
Angle of PCB/wire connection	0°/180° (horizontal)
Type of attachment to PCB	Connecting contact
Electrical connection type to PCB	Solder
Cross section single wire from	0.2 mm ²
Cross section single wire to	2.5 mm ²
Cross section stranded wire from	0.2 mm ²
Cross section stranded with ferrule to	2.5 mm ²
Cross section stranded wire to	2.5 mm ²
Cross section stranded with ferrule from	0.2 mm ²
Rated wire cross section to (AWG)	12
Rated wire cross section from (AWG)	22
Stripping length	7 mm
Screw size	M 3
Torque	0.5

MATERIALS

Housing material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-30 °C
Operating temperature to	105 °C
Screw material	Steel
Clamp material	Brass
Wire protection	Stainless steel

APPROVALS

UL test standard	UL 1059
Rated voltage UL	300 V
Rated current UL	20 A
cUL test standard	CSA 22.2 No.158
Rated voltage cUL	300 V

Rated current cUL	20 A
VDE test standard	DIN EN 60998
Rated voltage VDE	250 V
Rated current VDE	24 A
Recommended wave solder duration max	4 s
Recommended wave solder duration min	3 s
Recommended wave soldering temperature	265 °C
Tariff code	85369010
Pack size	50
Weight	2.3 g
Connection cycles acc. to standard	5
Country of origin	QU
Current creepage resistance	CTI 600
Glow wire flammability index (GWFI)	GWFI 850
Glow wire ignition temperature (GWIT)	GWIT 775
GWFI after-glow time	30 s
GWIT exposure time	5 s
Insulation resistance	1*10 ¹³ Ω x cm



