

## PK 500

10143.1

PK 500/5/2V 2P PCB VERT GREEN



### PRODUCT DESCRIPTION

## TECHNICAL DATA

### GENERAL DATA

Type	PCB terminal
Pitch	5 mm
Colour	Green
Number of poles	2
Approvals	UL, cUL, VDE

### RATINGS

Rated current	17.5 A
Rated voltage	250 V
Rated cross section	1.5 mm <sup>2</sup>
Rated impulse voltage	2 kV
Overvoltage category	III
Contamination degree	3

### DIMENSIONS

Length	10 mm
Width	10.6 mm
Height	7.5 mm
Width left	3.1 mm
Width right	2.5 mm
Drillhole diameter	1.3 mm

Diameter of the connection pin	1 mm
Length of pin	4.5 mm

## CONNECTION DATA

Connector type/principle	Wire protection
Number of levels	1
Angle of PCB/wire connection	0°/180° (horizontal)
Type of attachment to PCB	Connecting contact
Electrical connection type to PCB	Solder
Cross section single wire from	0.2 mm <sup>2</sup>
Cross section single wire to	1.5 mm <sup>2</sup>
Cross section stranded wire from	0.2 mm <sup>2</sup>
Cross section stranded with ferrule to	1.5 mm <sup>2</sup>
Cross section stranded wire to	1.5 mm <sup>2</sup>
Cross section stranded with ferrule from	0.2 mm <sup>2</sup>
Rated wire cross section to (AWG)	14
Rated wire cross section from (AWG)	22
Stripping length	6 mm
Screw size	M 2,6
Torque	0.4

## MATERIALS

Housing material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-30 °C
Operating temperature to	105 °C
Screw material	Steel
Clamp material	Brass
Wire protection	Stainless steel

## APPROVALS

UL test standard	UL 1059
Rated voltage UL	300 V
Rated current UL	15 A
cUL test standard	CSA 22.2 No.158
Rated voltage cUL	300 V

Rated current cUL	15 A
VDE test standard	DIN EN 60998
Rated voltage VDE	250 V
Rated current VDE	17.5 A

Recommended wave solder duration max	4 s
Recommended wave solder duration min	3 s
Recommended wave soldering temperature	265 °C
Tariff code	85369010
Pack size	50
Weight	1.8 g
Connection cycles acc. to standard	5
Country of origin	QU
Current creepage resistance	CTI 600
Glow wire flammability index (GWFI)	GWFI 850
Glow wire ignition temperature (GWIT)	GWIT 775
GWFI after-glow time	30 s
GWIT exposure time	5 s
Insulation resistance	$1 \cdot 10^{13} \Omega \times \text{cm}$



