

**PK 360**

10401.1

PK 360/7.5/2V 2P PCB VERT RC



## PRODUCT DESCRIPTION

**TECHNICAL DATA****GENERAL DATA**

Type	PCB terminal
Pitch	7.5 mm
Colour	Green
Number of poles	2
Approvals	UL, cUL, VDE

**RATINGS**

Rated current	17.5 A
Rated voltage	750 V
Rated cross section	1.5 mm <sup>2</sup>
Rated impulse voltage	3 kV
Overvoltage category	III
Contamination degree	3

**DIMENSIONS**

Length	9 mm
Width	15.6 mm
Height	13.5 mm
Width left	4.35 mm
Width right	3.75 mm
Drillhole diameter	1.3 mm

Diameter of the connection pin	1 mm
Length of pin	3.5 mm

## CONNECTION DATA

Connector type/principle	Screw
Number of levels	1
Angle of PCB/wire connection	0°/180° (horizontal)
Type of attachment to PCB	Connecting contact
Electrical connection type to PCB	Solder
Cross section single wire from	0.14 mm <sup>2</sup>
Cross section single wire to	2.5 mm <sup>2</sup>
Cross section stranded wire from	0.14 mm <sup>2</sup>
Cross section stranded with ferrule to	1.5 mm <sup>2</sup>
Cross section stranded wire to	1.5 mm <sup>2</sup>
Cross section stranded with ferrule from	0.25 mm <sup>2</sup>
Rated wire cross section to (AWG)	12
Rated wire cross section from (AWG)	22
Stripping length	6 mm
Screw size	M 3
Torque	0.5

## MATERIALS

Housing material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-30 °C
Operating temperature to	105 °C
Solder lug	Brass
Screw material	Steel
Clamp material	Brass

## APPROVALS

UL test standard	UL 1059
Rated voltage UL	300 V
Rated current UL	16 A
cUL test standard	C22.2 No 158
Rated voltage cUL	300 V

Rated current cUL	16 A
VDE test standard	DIN EN 60998
Rated voltage VDE	750 V
Rated current VDE	17.5 A

Recommended wave solder duration max	4 s
Recommended wave solder duration min	3 s
Recommended wave soldering temperature	265 °C
Tariff code	85369010
Pack size	50
Weight	2.9 g
Connection cycles acc. to standard	5
Country of origin	QU
Current creepage resistance	CTI 600
Glow wire flammability index (GWFI)	GWFI 850
Glow wire ignition temperature (GWIT)	GWIT 775
GWFI after-glow time	30 s
GWIT exposure time	5 s
Insulation resistance	1*10 <sup>13</sup> Ω x cm



