

PK 710

10467.1

PK 710/7.5/2V 2P PCB VERT GREEN



PRODUCT DESCRIPTION

TECHNICAL DATA**GENERAL DATA**

Type	PCB terminal
Pitch	7.5 mm
Colour	Green
Number of poles	2
Approvals	UL, cUL, VDE

RATINGS

Rated current	24 A
Rated voltage	750 V
Rated cross section	2.5 mm ²
Rated impulse voltage	3 kV
Overvoltage category	III
Contamination degree	3

DIMENSIONS

Length	10.5 mm
Width	15.6 mm
Height	19 mm
Width left	4.35 mm
Width right	3.75 mm
Drillhole diameter	1.3 mm

Diameter of the connection pin	0.9 mm
Length of pin	4 mm

CONNECTION DATA

Connector type/principle	Screw
Number of levels	1
Angle of PCB/wire connection	0°/180° (horizontal)
Type of attachment to PCB	Connecting contact
Electrical connection type to PCB	Solder
Cross section single wire from	0.2 mm ²
Cross section single wire to	4 mm ²
Cross section stranded wire from	0.2 mm ²
Cross section stranded with ferrule to	2.5 mm ²
Cross section stranded wire to	2.5 mm ²
Cross section stranded with ferrule from	0.25 mm ²
Rated wire cross section to (AWG)	12
Rated wire cross section from (AWG)	30
Stripping length	8 mm
Screw size	M 3
Torque	0.5

MATERIALS

Housing material	Polyamide 6.6
Flammability class	UL94-V0
Operating temperature from	-30 °C
Operating temperature to	105 °C
Solder lug	Copper alloy
Screw material	Steel
Clamp material	Brass

APPROVALS

UL test standard	UL 1059
Rated voltage UL	300 V
Rated current UL	6 A
cUL test standard	C22.2 No 158
Rated voltage cUL	300 V

Rated current cUL	6 A
VDE test standard	DIN EN 60998
Rated voltage VDE	750 V
Rated current VDE	24 A

Recommended wave solder duration max	4 s
Recommended wave solder duration min	3 s
Recommended wave soldering temperature	265 °C
Tariff code	85369010
Pack size	50
Weight	4.7 g
Connection cycles acc. to standard	5
Country of origin	QU
Current creepage resistance	CTI 600
Glow wire flammability index (GWFI)	GWFI 850
Glow wire ignition temperature (GWIT)	GWIT 775
GWFI after-glow time	30 s
GWIT exposure time	5 s
Insulation resistance	1*10 ¹³ Ω x cm



