OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

HIGH TEMPERATURE

Progress® HT

1000.17.92
Gland NPB, High temp, M16, ø8…10.5mm



- Single or two piece sealing inserts
- Great flexibility
- -40°C…+200°C
- IP 68 up to 10 bar, IP69

PRODUCT DESCRIPTION

The High temperature Progress® range of nickel-plated brass glands are a tried and tested solution for cable entry in industrial applications and use an FPM seal insert, giving them a temperature range of -40°c to 200°C.

This range is available with two pieces inserts which offer a wide cable clamping range or for the best fit, one piece inserts that are designed for a smaller overall cable size range.

The outstanding compression technology is designed to be used in a wide range of applications and guarantees an effective seal with excellent cable-protecting strain relief, even where vibration is an issue.

The Progress® glands are available with a short or long entry thread metric, Pg, imperial or NPT and can be used with existing threaded holes or with a lock nut.

When tightening the gland, a small bulge in the sealing insert confirms the correct tightening torque has been reached, giving positive visible feedback to the installer.

The integrated retaining grooves in the lower part of the gland and in the sealing insert prevent the insert from twisting and becoming deformed.

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M16
Insert Type	Two-Piece
Cable diameter inner min	6 mm
Cable diameter inner max	8 mm
Cable diameter min	8 mm
Cable diameter max	10.5 mm
IP class	IP 68 (up to 10 bar), IP 69 further protection

DIMENSIONS

Thread pitch	1.5
Thread length	5 mm
Height (H)	22 mm
Spanner width (AF)	18 mm

MATERIALS

Material	Nickel-plated brass
Materials O-ring	FPM
Material of seals	FPM
Temperature range	-40°C … +200°C

APPROVALS

Approvals	CE, SEV, VDE, EAC, DNV
Strain relief	Version A acc. to EN 62444

ADDITIONAL DATA

Pack size	50
Country of origin	CH
Tariff code	74199949
Weight	19.88 g





