


ULTRA FLAT STAINLESS STEEL

Progress® ultraFLAT A2, Progress® ultraFLAT
A2 HT

1040.25.96.30.110

Gland stainless steel A2 ultraFLAT, EHEDG, M25, ø8...
11mm

- Flush fitting
- A2 - AISI 303
- FKM seals (FDA approved) or FPM seals
- EHEDG certified for the food industry
- IP68 up to 10 bar, IP69



PRODUCT DESCRIPTION

The Progress® ultraFLAT A2 is a stainless steel flush mount cable gland designed application areas such as:

- Clean rooms
- Food industry
- Anti-vandalism
- Aesthetic design
- High temperature applications -40°C to +200°C

The ultra-flat construction of the Progress® ultraFLAT cable gland prevents any manipulation from the outside. No external nut is visible on the external side of the gland.

In addition, the cable gland has been designed with an attractive shape, which is less industrial looking and more 'design' friendly to the eye.

The Progress® ultraFLAT cable gland offers very little surface trap points for contamination, so is ideally suited for wash down environments, which is crucial for cleanroom and food applications. These food EHEDG certified glands are easily recognised, as they have a blue coloured FKM seal which have been cleared by the FDA.

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M25
Insert Type	One-Piece
Cable diameter min	8 mm
Cable diameter max	11 mm
IP class	IP 68 (up to 10 bar), IP 69 further protection

DIMENSIONS

Thread pitch	1.5
Thread length	25 mm
Height (H)	5.5 mm
Spanner width (AF)	30 mm
External diameter (□A)	32 mm
Wall thickness	5 mm max.

MATERIALS

Material	Stainless steel A2
Material of seals	FKM
Inner-nut material	Nickel-plated brass
Sealing washer material	FKM
Temperature range	-40°C ... +200°C

APPROVALS

Approvals	CE
Strain relief	Version A acc. to EN 62444
Certificate	EHEDG

ADDITIONAL DATA

Pack size	20
Country of origin	CH
Tariff code	74199949
Weight	88.35 g

