OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# EMC - CONTACT SLEEVE

Progress® MS EMC

1080.09.100
Gland EMC NPB, sleeve, Pg 9, ø7.7…10mm



- Permenant contact pressure
- 360° contact sleeve construction
- -40°C…+100°C
- IP68 up to 10 bar, IP69K

**PRODUCT DESCRIPTION**

# TECHNICAL DATA

## GENERAL DATA

| | |
|---|---|
| **Thread Size (G)** | PG 9 |
| **Insert Type** | One-Piece |
| **Cable diameter min** | 8 mm |
| **Cable diameter max** | 10 mm |
| **IP class** | IP 68 (up to 10 bar), IP 69 further protection |

## DIMENSIONS

| | |
|---|---|
| **Thread length** | 6 mm |
| **Height (H)** | 25 mm |
| **Spanner width (AF)** | 18 mm |

## MATERIALS

| | |
|---|---|
| **Material** | Nickel-plated brass |
| **Materials O-ring** | NBR |
| **Material of seals** | TPE |
| **Contact sleeve material** | Nickel-plated brass |
| **Temperature range** | -40°C ... +100°C |

## APPROVALS

| | |
|---|---|
| **Approvals** | cRUus, EAC |

## ADDITIONAL DATA

| | |
|---|---|
| **Pack size** | 50 |
| **Country of origin** | CH |
| **Tariff code** | 74199949 |
| **Weight** | 23.48 g |

