OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

EMC - ANTI-KINK PROTECTION

Progress® MS EMC FKM

1080.17.52.080
Gland EMC NPB, sleeve, M16, spring sleeve, ø6…8mm



- Permenant contact pressure
- 360° contact sleeve construction
- Stainless steel spring
- -40°C…+100°C
- IP68

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M16
Insert Type	One-Piece
Cable diameter min	6 mm
Cable diameter max	8 mm
IP class	IP 68, IP 69 further protection

DIMENSIONS

Thread pitch	1.5
Thread length	5 mm
Height (H)	69 mm
Spanner width (AF)	18 mm

MATERIALS

Material	Nickel-plated brass
Materials O-ring	NBR
Material of seals	TPE
Nozzle material	Stainless steel A2

Temperature range	-40°C ... +100°C

APPROVALS

Approvals	SEV, CE, DNV, EAC, VDE
Strain relief	Version A acc. to EN 62444

ADDITIONAL DATA

Pack size	10
Country of origin	CH
Tariff code	74199949
Weight	51.9 g

