OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

EMC - CONTACT SLEEVE

Progress® MS EMC

1080.32.210
Gland EMC NPB, sleeve, M32, ø18…21mm



- Permenant contact pressure
- 360° contact sleeve construction
- -40°C…+100°C
- IP68 up to 10 bar, IP69K

PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Thread Size (G)	M32
Insert Type	One-Piece
Cable diameter min	18 mm
Cable diameter max	21 mm
IP class	IP 68 (up to 10 bar), IP 69 further protection

DIMENSIONS

Thread pitch	1.5
Thread length	8 mm
Height (H)	32 mm
Spanner width (AF)	36 mm

MATERIALS

Material	Nickel-plated brass
Materials O-ring	NBR
Material of seals	TPE
Contact sleeve material	Nickel-plated brass

Temperature range	-40°C ... +100°C

APPROVALS

Approvals	SEV, CE, cRUus, DNV, EAC, VDE
Strain relief	Version A acc. to EN 62444

ADDITIONAL DATA

Pack size	25
Country of origin	CH
Tariff code	74199949
Weight	110.52 g

