**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# STAINLESS STEEL HIGH TEMPERATURE

## Progress®S2 HT, Progress®S4 HT

1100.29.96
Gland stainless steel A2, High temp, Pg 29, long, ø19…27.5mm



- A2 -AISI303, A4 - AISI 316L
- Identification marks
- -40°C…+200°C
- IP68 up to 10 bar, IP69

### PRODUCT DESCRIPTION

The Progress® range of stainless steel glands are highly corrosion-proof and ideal for use in the food, chemical industry, as well as any environmentally challenging applications, such as tunnels and offshore.

The high temperature products include A2 (DIN EN 1.4305/AISI303) and acid resistant A4 CrNiMo (DIN EN 1.4435/AISI316L).

The FPM seals can operate in temperatures from -40°C to +200°C.

All AGRO stainless steel glands have a series of grooves in the main gland & cap to easily identify the material.

This range is available with two pieces inserts which offer a wide cable clamping range or for the best fit, one piece inserts that are designed for a smaller overall cable size range.

The outstanding compression technology is designed to be used in a wide range of applications and guarantees an effective seal with excellent cable-protecting strain relief, even where vibration is an issue.

The Progress® stainless range is available with a short or long entry thread in metric or Pg and can be used with existing threaded holes or with a lock nut.

When tightening the gland, a small bulge in the sealing insert confirms the correct tightening torque has been reached, giving positive visible feedback to the installer.

The integrated retaining grooves in the lower part of the gland and in the sealing insert prevent the insert from twisting and becoming deformed.

# TECHNICAL DATA

## GENERAL DATA

| | |
|---|---|
| **Thread Size (G)** | PG 29 |
| **Insert Type** | Two-Piece |
| **Cable diameter inner min** | 19 mm |
| **Cable diameter inner max** | 23 mm |
| **Cable diameter min** | 23 mm |

| | |
|---|---|
| **Cable diameter max** | 27.5 mm |
| **IP class** | IP 68 (up to 10 bar), IP 69 further protection |

## DIMENSIONS

| | |
|---|---|
| **Thread length** | 12 mm |
| **Height (H)** | 28 mm |

## MATERIALS

| | |
|---|---|
| **Material** | Stainless steel A2 |
| **Materials O-ring** | FPM |
| **Material of seals** | FPM |
| **Temperature range** | -40°C … +200°C |

## APPROVALS

| | |
|---|---|
| **Approvals** | EAC |
| **Identification** | 1 groove |

## ADDITIONAL DATA

| | |
|---|---|
| **Pack size** | 25 |
| **Country of origin** | CH |
| **Tariff code** | 73269023 |
| **Weight** | 122.82 g |

