


EMC COMBINATION CONDUIT GLANDS

Progress Kombi EMC

1165.84.32.34

Combination EMC conduit gland M32, long, ø12...
20mm



- EMC Conduit glands
- Copper braid versions for ROHRflex corrugated conduit
- Rail approved versions to EN 45545
- IP68

PRODUCT DESCRIPTION

AGRO Combination EMC conduit glands are an ideal solution if you want to introduce cables inside a conduit into an enclosure and at the same time want a secure, seal and add strain relief for the cables inside, while maintaining EMC immunity

The integrated cable gland achieves excellent sealing (IP 68) inside the conduit. This ensure the enclosure stay free from water and condensation ingress.

Special version for copper braids, suitable for Flexa ROHRflex.

For railway applications where cables are laid in conduits in order to protect them from impacts or manipulation – the same requirements apply as for cable glands: the combination conduit glands must be equipped with a sealing insert made of special TPE according to the requirements of EN 45545.

These are available on request and the part number is just prefixed by a capital 'F'.

TECHNICAL DATA

GENERAL DATA

| | |
|--------------------|---|
| Thread Size (G) | M32 |
| Insert Type | One-Piece |
| Cable diameter min | 12 mm |
| Cable diameter max | 20 mm |
| IP class | IP 68 (together with ROHRflex® corrugated tube) |

DIMENSIONS

| | |
|---------------|-------|
| Thread pitch | 1.5 |
| Thread length | 13 mm |

| | |
|--------------------|---------|
| Height (H) | 36.5 mm |
| Spanner width (AF) | 36 mm |

MATERIALS

| | |
|-------------------------|---------------------|
| Material | Nickel-plated brass |
| Materials O-ring | NBR |
| Contact sleeve material | Nickel-plated brass |
| Temperature range | -40°C ... +120°C |

ADDITIONAL DATA

| | |
|-------------------|----------|
| Pack size | 25 |
| Country of origin | CH |
| Tariff code | 74199949 |
| Weight | 146.6 g |

